


IP67 Halogen Stainless Steel Spot/Floodlight

- Wireless remote communication
- 316 stainless steel base, 304 stainless steel head
- 350° horizontal, 60° vertical two speed movement

Peak beam intensity	165,000 CP spot
Amp draw	Spot 8.3A, flood 7.5A @ 12V Spot 4.15A, flood 3.75A @ 24V
Power (Input voltage)	12V & 24V
Bulb	H4 halogen
Dimensions	9.875"H x 4.75"W x 8.35"L
Weight	6 lbs.
IP Rating	IP67 (see inside back cover)



3 YEAR WARRANTY

Remote Options




Part #	22250-R	22350-R
Voltage	12V	24V
Power	12V DC	24V DC
Remote Specifications	Wireless Communication Bridge Remote	
Wireless range	100 ft (30m)	
Dimensions	2.2"W x 3.65"H x 0.9"D	
Housing material	ASA	
Button material	Silicone (glow in the dark)	

Description	Part #
12V Spot/Flood with Remote (22250-R)	22050A
12V Spot/Flood Only	22051A
24V Spot/Flood with Remote (22350-R)	22150A

IP67 LED Stainless Steel Spotlight

- Wireless remote communication
- 316 stainless steel base, 304 stainless steel head
- 350° horizontal, 60° vertical two speed movement

Light Output	92,000 CD
Amp Draw	3A @12V DC 1.5A @24V DC
Power (Input voltage)	12V or 24V DC
# of LEDS	12
Dimensions	9.875"H x 4.75"W x 8.35"L
Weight	11.36 lbs (5.2 kg)
IP Rating	IP67 (see inside back cover)



3 YEAR WARRANTY

Remote Options



Part #	23250-R	23350-R
Voltage	12V	24V
Power	12V DC	24V DC
Remote Specifications	Wireless Communication Bridge Remote	
Wireless range	100 ft (30m)	
Dimensions	2.2"W x 3.65"H x 0.9"D	
Housing material	ASA	
Button material	Silicone (glow in the dark)	

Description	Part #
12V Spotlight with Remote (23250-R)	23050A
12V Spotlight Only	23051A
24V Spotlight with Remote (23350-R)	23150A